



2024 Pete Fiandaca Memorial Rules

Open Street Stocks

- Tires – Hoosier 790 (26.5” or 27”)
- Carburetors: Built Motor - 4412 / 602 Sealed Crate - 80541HP
- Weight: 602 Sealed Crate – 3050 lbs. / Built Motor - 3150 lbs.
- 10 ½ Clutch & Flywheel (Must Be Magnetic Steel)
- No Canister or Adjustable Shocks

Open 4-Cylinder Pure Stocks

- 1 Pound Per CC (2000 lbs. minimum)
- 400 Treadwear Tire
- OEM Suspension (Except Springs)

Open Six Shooters

- American Made / V6 / FWD
- Weight: Up To 215 HP – 3000 lbs. / 216 And Up (Max 250 HP) – 3100 lbs.
- 400 Treadwear (All Same Size)

Open Ridge Runners

- Weight: Coil Spring 305 – 3000 lbs. / Coil Spring 350 – 3200 lbs.
Leaf Spring & Next Gen 4 305 – 3200 lbs.
Leaf Spring & Next Gen 4 350 – 3400 lbs.
- Carburetor: 500 CFM Rochester 2G (MUST Pass Gauge)
- Manifolds on Exhaust
- Automatic Transmission with Functioning 12” Torque Converter
- Tires: Hoosier 790 (26.5” or 27”)

Open Mini Stocks

- Weight: Up To 1.6L – 2150 lbs. / 1.7L And Up – 2200 lbs.
- Maximum Spoiler Size: 5” X 58”
- Tires – Hoosier 800 (23” Or 23.5”)